

# 27WON

## GEN-6-400 Air Filter Replacement

A how-to guide on replacing the air filter element for your 27WON cold air intake system for the 2016-2021 Honda Civic equipped with the 1.5L Turbo engine.

Written By: Josh Rivas



## INTRODUCTION

In this installation guide we have provided step-by-step instructions to remove and replace the 27WON Air Filter for 27WON Intake System.



### TOOLS:

- [10mm Socket](#) (1)
- [3/8" Ratchet](#) (1)
- [Allen Wrench 3mm](#) (1)



### PARTS:


- [Air Filter](#) (1)

## Step 1 — Getting Started



- First and foremost; **THANK YOU** for being a part of the 27WON Family. We hope to **REDEFINE** your experience of the aftermarket well beyond your first purchase of a new part
- ⓘ The following instructions were written on 2018 Civic Si for all 10th gen turbo Civic's with the 1.5L and 27WON CAI system already installed


## Step 2 — Locate Air Filter



- Open the hood and locate your airbox and airbox lid




### Step 3 — Remove Air Box Lid



- Using the 3mm Allen tool remove the 4x screws securing the lid to the airbox
- Remove the lid and set aside with the 4x screws for reinstall later

### Step 4 — Remove Air Filter from Airbox



- Using the 10mm socket and ratchet loosen the 10mm lock nut on the t-bolt clamp
- Pull filter forward off of velocity stack and lift up and out of airbox

## Step 5 — Clean Airbox



- Now is a great time to clean your air box. Simply use a microfiber towel to wipe down the inside of you airbox to remove any dust


## Step 6 — Securing Air Filter to Airbox Warning



- ⓘ The next step explains how to reinstall your air filter.
- ⚠ When re-installing your air filter be careful not to deform the air box to a point of deformation by over-tightening the clamp. Doing so can cause the air box to crack and the air filter to fall off



## Step 7 — Install New Air Filter




- Swap the clamp over from the old filter to the new filter
- Install filter with clamp into the airbox and over the velocity stack
- Verify the filter is fully over the velocity stack all the way around
- ⚠ Filter can fall off if this is not done correctly
- Orient clamp with nut as shown. Tighten the t-bolt clamp down

## Step 8 — Install Airbox Lid



- Reinstall the airbox lid and secure it with the 4x screws removed earlier. Torque the 4x screws to snug
- ⓘ **"Torque to snug"** is defined as 1/4 to 1/2 more rotation after setting resistance is felt

## Step 9 — Service Your Old Filter



- This completes the replacement of your 27WON Air Filter
- If you would like to see how to clean your filter so you have a fresh filter to swap in next time check out this video -  
<https://youtu.be/nE7diTel4Gw>
- Stay Connected with the latest developments with the 27WON Monthly Newsletter:  
<https://store.27won.com/27won-newsletter...>
- See the latest Products and Tech Videos from 27WON with a quick Subscribe:  
<https://www.youtube.com/channel/UCF7uI0N...>